



Product	Name	Speaker Cable				
Conductor	Material	Bare Copper			Electrical Characteristics (20°C)	Max.Conductor DC Resista at 20°C (Ω/M) 0.025
	Nom.O.D. (mm)	2x24/0.20 (2x0.75mm ²)	Up	+0.02		Rated Voltage (V) ≤36
	External O.D.	2.5mm×2c	Down	-0.02	Sheath Physical Properties	Rated Temperature(°C) 70°C
			Up	+0.05		
Jacket	Surface	Smooth			View	
		Material	PVC(complies RoHS Reach) CPR(Eca)			
				Page		

no.	Packaging	Length (m)	color
15093	Cable coil	10	red/black
15094	Cable coil	25	red/black
15080	Cable coil	50	red/black
15083	Cable Reel	100	red/black
15122	Cable coil	10	transparent
15123	Cable coil	25	transparent
15124	Cable coil	50	transparent
15125	Cable Reel	100	transparent
15112	Cable coil	10	white
15113	Cable coil	25	white
15104	Cable coil	50	white
15103	Cable Reel	100	white

Inner conductor material OFC CU (oxygen-free copper)
Eca Fire class (CPR) according to DIN EN 13501-6

Änderungen		Datum	Name
Datum	Name	gez.:	TL
12.08.2021	TL	gepr.:	
		Norm:	
Änderungen vorbehalten / Subject to change			

Bezeichnung	Blatt
LSK 2x0,75mm ²	1/1
Zeichnungs-Nr.: 15103 15104 15113 15112 15125 15124 15123 15122 15083 15080 15094 15093	von

