

Cable	Attenuation [dB]						
	10 MHz	100 MHz	500 MHz	1 GHz	2 GHz	3 GHz	6 GHz
N-Male to N-Male cable, 75 cm, RG58	0.06	0.15	0.36	0.58	0.73	1.01	1.81
N-Male to SMA-Male, 75 cm, RG58	0.06	0.15	0.36	0.58	0.73	1.02	1.83
N-Male to BNC-Male, 75 cm, RG58	0.06	0.15	0.36	0.58	0.81	1.15	2.14
SMB-Female to SMA-Male, 75 cm, RG-316U	0.03	0.26	0.63	0.91	1.33	1.74	3.91
N-Male to N-Male, 75 cm, RG223	0.06	0.13	0.31	0.45	0.57	0.81	1.26
N-Male to SMA-Male, 75 cm, RG223	0.06	0.13	0.3	0.45	0.58	0.84	1.29
N-Male to BNC-Male, 75 cm, RG223	0.06	0.15	0,33	0.55	0.77	1.05	1.97
N-Male to N-Male cable, 5m, RG223	0.11	0.62	1.6	2.6	3.7	4.6	6.8
N-Male to N-Male cable, 5 m, RG213	0.07	0.32	0.99	1.9	2.6	3.4	5.9
N-Male to N-Male cable, 5 m, RG142	0.16	0.53	1.4	2.4	3.4	4.2	6
N-Male to N-Male cable, 10 m, RG142	0.67	1.11	3.6	6.7	8.6	10.2	14.1
N-Male to SMA-Male, 75cm, low loss, double shielded RG142	0.06	0.13	0.3	0.45	0.57	0.78	1.21
N-Male to N-Male, 75cm, low loss, double shielded RG142	0.06	0.12	0.29	0.42	0.54	0.73	1.2
SMA-Male to SMA-Male, 75cm, low loss, double shielded RG142	0.06	0.13	0.3	0.45	0.57	0.78	1.23