



Product	Name	Speaker Cable				
Conductor	Material	Copper Coated Aluminum			Electrical Characteristics (20°C)	Max.Conductor DC Resistanc at 20°C (Ω/M) 0.019
	Nom.O.D. (mm)	2x30/0.25 (2x1.5mm ²)	Up	+0.02		Rated Voltage (V) ≤36V
			Down	-0.02		
	Jacket	External O.D.	3mm×2c	Up	+0.05	Sheath Physical Properties
Down				-0.05		
Surface		Smooth		View		
Material		PVC(complies RoHS Reach) CPR(Eca)		Drawn By		
					Page	

no.	Packaging	Length (m)	color
67720	Cable coil	10	transparent
67721	Cable coil	25	transparent
67722	Cable coil	50	transparent
15019	Cable Reel	100	transparent
67747	Cable coil	10	white
67748	Cable coil	25	white
67749	Cable coil	50	white
27523	Cable Reel	100	white
67732	Cable coil	10	red/black
67733	Cable coil	25	red/black
67734	Cable coil	50	red/black
15023	Cable Reel	100	red/black

Eca Fire class (CPR) according to DIN EN 13501-6

Änderungen			Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.:	12.08.2021	TL	LSK 2x1,5mm ²	1/1
12.08.2021	TL	gepr.:				
		Norm:			Zeichnungs-Nr.:27523 15019 15023 67749 67722 67734 67748 67721 67733 67747 67720 67732	von
		Änderungen vorbehalten / Subject to change				

