



Product	Name	Speaker Cable			Electrical Characteristics (20°C)	Max. Conductor DC Resistan at 20°C (Ω/M) 0.008
Conductor	Material	Bare Copper				
	Nom.O.D. (mm)	2x80/0.20 (2x2.5mm ²)	Up	+0.02		
Jacket	External O.D.	4mm×2c	Down	-0.02	Sheath Physical Properties	Rated Temperature(°C) 70°C
			Up	+0.05		
	Surface	Smooth		View		
	Material	PVC(complies RoHS Reach) CPR(Eca)		Drawn By		
					Page	

no.	Packaging	Length (m)	color
15099	Cable coil	10	red/black
15100	Cable coil	25	red/black
15082	Cable coil	50	red/black
15085	Cable Reel	100	red/black
15130	Cable coil	10	transparent
15131	Cable coil	25	transparent
15132	Cable coil	50	transparent
15133	Cable Reel	100	transparent
15117	Cable coil	10	white
15116	Cable coil	25	white
15108	Cable coil	50	white

Inner conductor material OFC CU (oxygen-free copper)
Eca Fire class (CPR) according to DIN EN 13501-6

Änderungen			Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.:	12.08.2021	TL	LSK 2x2,5mm ²	1/1
12.08.2021	TL	gepr.:				
		Norm:			Zeichnungs-Nr.: 15108 15116 15117 15133 15132 15131 15130 15085 15082 15100 15099	von
		Änderungen vorbehalten / Subject to change				

